

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name **ALKACLEAN**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the product

**LIQUID CHLORINATED ALKALI
LIQUID CHLORINATED ALKALI
CLEANING AND DISINFECTION
FOR THE MILKING MACHINE AND BULK TANK**

1.3. Details of the supplier of the safety data sheet

Company identification

**Manufacturer: HYPRED S.A.
57, Boulevard Jules VERGER B.P. 10180
35803 DINARD CEDEX - FRANCE
Tél : 33 2 99 16 50 00
Fax : 33 2 99 16 50 20
e-mail : hypred@hypred.fr**

For information regarding this safety data sheet, please contact :
hypred.regulatory@roullier.com

1.4. Emergency telephone number

Emergency phone number

**Emergency direct number (24 hours a day, 7 days a week) : (+)1-760-476-3961
Access code : 333021**

**Call your medical practitioner LONDON (Information available at the National
Poison Unit - Guy's Hospital)**

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation 1272/2008/EC:

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

The mixture meets the classification criteria provided for under Regulation (EC) No 1272/2008.

Skin corrosion - Category 1A	H314: Causes severe skin burns and eye damage.
Acute toxicity to the aquatic environment - Category 1	H400: Very toxic to aquatic life.
Chronic toxicity to the aquatic environment - Category 2	H411: Toxic to aquatic life with long lasting effects.
Substance corrosive to metals - Category 1	H290: May be corrosive to metals. EUH 031: Contact with acids liberates toxic gas.

Classification according to Directive 1999/45/EEC:

The mixture meets the classification criteria provided for under Directive 1999/45/EEC.

C : CORROSIVE, N : DANGEROUS FOR THE ENVIRONMENT

R31 : Contact with acids liberates toxic gas.


R35 : Causes severe burns.

R50 : Very toxic to aquatic life.

2.2. Label elements

Labelling according to 1272/2008/EC Regulation:

Hazard pictograms(s) :



Signal word :

Danger

Hazard statement(s) :

H290: May be corrosive to metals.

H314: Causes severe skin burns and eye damage.

H410: Very toxic to aquatic life with long lasting effects.

EUH 031: Contact with acids liberates toxic gas.

Precautionary statement(s) :

P273: Avoid release to the environment.

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P301 + P330 + P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
 P303 + P361 + P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310: Immediately call a POISON CENTER or doctor/physician.
 P391: Collect spillage.
 P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3. Other hazards

No additional information available.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable as this involves a mixture.

3.2. Mixtures

Chemical nature of the mixture : LIQUID CHLORINATED ALKALI

Substance(s)	CAS number(s)	EINECS number(s)	No registration REACH	Classification according to 67/548/EEC or 1999/45/EC	Classification according to Regulation 1272/2008/EC	Type
5% <= Sodium hydroxide < 15%	1310-73-2	215-185-5	01-2119457892-27	C , R35	Skin Corr. 1A H314 Met. Corr. 1 H290	(1) (2)
5% <= Sodium hypochlorite < 10%	7681-52-9	231-668-3	Biocidal active substance, regarded as already registered	C N , R31 R34 R37 R50	Met. Corr. 1 H290 Skin Corr. 1B H314 STOT SE 3 H335 Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M Factor (Acute) 10 M Factor (Chronic) 1	(1)

Type

(1) : Substance classified as hazardous for health and/or the environment

(2) : Substance with an exposure limit at the work station.

Substance of very high concern candidate for the authorisation procedure:

(3) : Substance considered as PBT (persistent, bioaccumulable, toxic)

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

- (4) : Substance considered as vPvB (very persistent, very bioaccumulable)
- (5) : Substance considered as carcinogenic category 1A
- (6) : Substance considered as carcinogenic category 1B
- (7) : Substance considered as mutagenic category 1A
- (8) : Substance considered as mutagenic category 1B
- (9) : Substance considered as reprotoxic category 1A
- (10) : Substance considered as reprotoxic category 1B
- (11) : Substance considered as endocrine disrupter

Full text of R-, H- and EUH- phrases see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General indications:

Take the contaminated clothes and shoes off immediately. Wash them before wearing them again.
In case of faintness , get medical advice/attention. Show this safety data sheet to the doctor.

In the event of inhalation :

Bring to fresh air.
Put into practice respiratory help procedure if needed and get medical advice immediately.

In the event of contact with the skin :

Take off immediately all contaminated clothing.
Wash immediately with plenty of water for 15 minutes at least.
Immediately call a POISON CENTER or doctor/physician.

In the event of contact with the eyes :

Rinse at once with a soft stream of water for at least 15 minutes, eyes wide open.
Remove contact lenses if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.

In the event of ingestion :

Rinse mouth.
Do NOT induce vomiting.
Send to hospital.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact : Corrosive : Causes severe burns.

Eye contact : Causes serious eye damage.

Ingestion : Causes severe burns in mouth and digestive tract.
Risk of perforating digestive tracts.

Inhalation : May cause a respiratory system irritation.

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

4.3. Indication of any immediate medical attention and special treatment needed

Treatments : Symptomatic treatment

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media :

Agents compatible with other products involved into fire.

Unsuitable extinguishing media :

None from our knowledge.

5.2. Special hazards arising from the substance or mixture

ALKACLEAN is non-flammable.

However, in contact with certain metals (aluminium, zinc...), release of flammable and/or explosive hydrogen if ignited.

5.3. Advice for firefighters

Wear independent respiratory equipment and protective suit.

Collect contaminated firefighting water separately, must not be discharged into the drains.

Keep containers cool by spraying with water if exposed to fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel :

Evacuate non-essential staff and those not equipped with individual protection apparatus.

6.1.2. For emergency responders :

Evacuate the personnel to a safe location.

Keep people upwind and away from the location of the flow/leak.

Use personal protection equipment.

6.2. Environmental precautions

Intervention limited to trained staff.

Do not discharge the product directly to sewer or to environment.

Take as soon as possible all incompatible materials away.

6.3. Methods and material for containment and cleaning up

Small spillage :

Pump in a reservoir of help.

Large spillage :

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

Never return spills in original containers for re-use.
 Keep in suitable, properly labelled and closed containers for disposal.
 Mark out, dyke up with an inert absorbant and pump in an emergency tank.

6.4. Reference to other sections

Respect protective measures presented at heading 8.
 Refer to section 13 for the elimination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe vapour.
 Avoid contact with skin, eyes and clothing.
 Do not eat, drink or smoke in work area. Avoid projections during use.
 Do not mix with an acid.
 Take off immediately all contaminated clothing.
 Operate in a well ventilated place.

7.2. Conditions for safe storage, including any incompatibilities

7.2.1. Storage :

Keep only in the original container.
 Keep container closed.
 Keep in a cool place.
 Keep away from products sensitive to chlorinated alkalis.

7.2.2. Packaging or wrapping materials :

High density polyethylene recommended.

7.3. Specific end use(s)

ALKACLEAN is for use as a biocide.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limit values :

Substance	Country	Type	Value	Unit	Comments	source
Chlorine	GBR	OEL Short term	0,5	ppm		International limit values for chemical agents
			1,5	mg/m ³		International limit values for chemical agents
Nitrogen trichloride	FRA	VLCT Short term	1,5	mg/m ³	Valeur limite de confort déterminée par l'INRS	
		VLEP 8h	0,5	mg/m ³	Valeur limite de confort déterminée par l'INRS	
Sodium hydroxide	GBR	OEL Short term	2	mg/m ³		International limit values for chemical agents

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

8.2. Exposure controls

Directive 98/24/EEC requires the employer to introduce risk management measures. If restricted or indicative regulatory limit values have been set for substances in section 8.1, the employer must act on the outcome of his chemical risk assessment by checking the professional exposure limit values for their compliance.

8.2.1. Appropriate engineering controls :

Ensure adequate ventilation.

Apply the necessary technical measures to comply with the professional exposure limit values.

8.2.2. Individual protection measures, such as personal protective equipment :

Eye/face protection :

Use safety glasses or facial screen in conformity with the EN 166 standard.



Hand protection :

Use chemical resistant gloves approved to EN 374.

Examples of preferred materials for insulating gloves:

Butyl rubber.

Nitril.

Neoprene.

PVC

Do not wear polyvinyl alcohol (PVA) gloves.



Skin protection :

Wear boots and a protective cloth with chemical resistance.



Respiratory protection :

None under normal conditions of use.

Thermal hazards :

Not applicable

Health measures :

Safety shower and eye wash fountain near to workplace.

After using, wash systematically all personal protective equipment.

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

8.2.3. Environmental exposure controls :

Do not discharge the product directly to sewer or to environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid
Colour	Yellow
Odour	Chlorinated
Odour threshold	Non available
Pure pH	Non available
pH value at 10g/l	12.4±0.2
Freezing point :	-20 °C
Boiling point	> 100 °C
Flash point	Not applicable
Evaporation rate:	Non available
Flammability	Not applicable
Vapour pressure	Non available
Vapour density	Non available
Mass density	1.2±0.01 g/cm ³
Relative density	1.2±0.01
Solubility in water	Soluble in water in all proportions
Partition coefficient: n-octanol/water	Not applicable
Auto-ignition temperature	Not applicable
Decomposition temperature	Non available
Viscosity	Non available
Explosive properties	Not applicable
Oxidising properties	Not applicable

9.2. Other information

No additional information.

SECTION 10: Stability and reactivity

10.1. Reactivity

Hazards linked to exothermal reactions.

10.2. Chemical stability

Stable in the recommended storage and handling conditions.

10.3. Possibility of hazardous reactions

Exothermic reactions with acids.

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

10.4. Conditions to avoid

Light, heat.

10.5. Incompatible materials

Light metals and/or colored.

Acids.

10.6. Hazardous decomposition products

Contact with acids liberates gaseous chlorine.

In contact with certain metals (aluminium, zinc...), release of flammable and/or explosive hydrogen if ignited.

These data are given for the concentrated mixture. The use of the mixture under its diluted form must be performed in conformity with data given by the technical data sheet and the technical adviser.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Substance-related data:

Acute toxicity

Sodium hypochlorite : LD 50 - oral rat > 2,000 mg/kg. - solutions, 12%< active chlorine<16% - MSDS supplier

Sodium hydroxide (50%) : Oral . The oral DL50 has not been determined given the corrosiveness of the substance. - MSDS supplier

Sodium hypochlorite : LD 50 - dermal rabbit > 2,000 mg/kg. - solutions, 12%< active chlorine<16% - MSDS supplier

Sodium hydroxide (50) : Dermal route . The dermal DL50 has not been determined given the corrosiveness of the substance. - MSDS supplier

Sodium hydroxide : LD 50 - dermal rat 1,350 mg/kg. - MSDS supplier

Skin corrosion/irritation

Sodium hydroxide (50%) : Cutaneous contact rat . Corrosive to the skin - MSDS supplier

Sodium hydroxide + Sodium hypochlorite : Skin irritation . Corrosive. - MSDS supplier

Serious eye damage/eye irritation

Sodium hydroxide (50%) : Eye contact : . corrosive to the eyes - MSDS supplier

Sodium hydroxide + Sodium hypochlorite : Eye irritation . Corrosive. - MSDS supplier

Respiratory tracts irritation

Sodium hydroxide (50%) : Respiratory tracts irritation . Fog inhalation is irritant for respiratory tract - MSDS supplier

Mutagenicity

Sodium hydroxide : . Not mutagenic - MSDS supplier

Carcinogenicity

Sodium hydroxide : mouse . Not carcinogenic - MSDS supplier

Mix-related data :

Acute toxicity

. Not determined

Skin corrosion/irritation

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

Skin corrosivity . The mixture should be considered as corrosive because of its extreme pH.

Serious eye damage/eye irritation

Ocular corrosivity . Causes serious eye damage according to the criteria of Regulation 1272/2008/EC.

Respiratory or skin sensitisation

Skin sensitisation . The mixture is not considered as a skin sensitizer according to 1272/2008/EC Regulation.

Respiratory sensitization . The mixture is not considered as a respiratory sensitizer according to 1272/2008/EC Regulation.

Mutagenicity

. The classification criteria are not met given the available data.

Carcinogenicity

. The classification criteria are not met given the available data.

Reproductive toxicity

. The classification criteria are not met given the available data.

Specific target organ toxicity - single exposure

. The classification criteria are not met given the available data.

Specific target organ toxicity - repeated exposure

. The classification criteria are not met given the available data.

Aspiration hazard

. The classification criteria are not met given the available data.

Most important symptoms and effects, both acute and delayed :

Skin contact : Corrosive : Causes severe burns.

Eye contact : Causes serious eye damage.

Ingestion : Causes severe burns in mouth and digestive tract.
Risk of perforating digestive tracts.

Inhalation : May cause a respiratory system irritation.

SECTION 12: Ecological information**12.1. à 12.4. Toxicity - Persistence and degradability - Bioaccumulative potential - Mobility in soil****Substance-related data:**

Acute toxicity

Sodium hydroxide : LC 50 - 96 h fishes (Gambusia affinis) 35 - 189 mg/L. - MSDS supplier

Sodium hypochlorite : EC 50 - 48h Aquatic invertebrates 0.01 - 0.1 mg/L. - solutions, 12%< active chlorine<16% - MSDS supplier

CHRONIC TOXICITY

Sodium hypochlorite : NOEC - 7days algae 0.002,1 mg/L. - MSDS supplier

Degradability

Sodium hydroxide (50%) : Biodegradability aerobic . Not applicable - MSDS supplier

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

Sodium hydroxide (50%) : Biodegradability anaerobic . Not applicable - MSDS supplier
Sodium hydroxide (50%) : Half life air 13 seconds. Degradation product = sodium carbonate - MSDS supplier
Sodium hydroxide (50%) : water. . Instantaneous ionization; Degradation products : salts - MSDS supplier
Sodium hydroxide (50%) : soil . Ionization / neutralization - MSDS supplier

Bioaccumulation

Sodium hydroxide (50%) : . Not applicable - MSDS supplier

Mobility

Sodium hydroxide (50%) : air . Instantaneous degradation - MSDS supplier
Sodium hydroxide (50%) : water. . Important solubility and mobility - MSDS supplier
Sodium hydroxide (50%) : soil/sediments . Important solubility and mobility; Contamination of ground water in case of rain - MSDS supplier

Mix-related data :

Acute toxicity

fishes . Not determined
EC 50 - 48h daphnia (Daphnia magna) (OCDE 202): 0.93 mg/L.
algae . Not determined

CHRONIC TOXICITY

. No data available.

Degradability

. The surface agents contained in this mix are in line with the requirements of the Detergent Regulation 648/2004/EC.

Bioaccumulation

. No data available.

Mobility

. No data available.

Conclusion :

The mixture is considered to be dangerous for the environment according to 1272/2008/EC Regulation.

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB

12.6. Other adverse effects

No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Treatment of the mixture :

Do not discharge the product directly to sewer or to environment.

Comply with Directive 2008/98/EC of 19/11/2008 relating to waste and to Decision 2000/532/EC (amended ultimately by Decision 2001/119/EC) that establishes a list of hazardous waste that must be taken to an approved centre.

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

Packaging treatment :

Rinse thoroughly the packaging with water and treat the effluent like wastes.

Comply with Directive 2008/98/EC of 19/11/2008 relating to waste and to Decision 2000/532/EC (amended ultimately by Decision 2001/119/EC) that establishes a list of hazardous waste that must be taken to an approved centre.

SECTION 14: Transport information

ROAD TRANSPORT:

Rail/Route (RID/ADR)

UN no : 1719

UN proper shipping name : CAUSTIC ALKALINE LIQUID, N.O.S. (Sodium hydroxide+Sodium hypochlorite)

Class : 8

Packing group : II

Hazard code : 80

Label : 8



Tunnel code : E

Environmental hazard : Yes (Sodium hypochlorite)

Special precautions for user : No information.


MARITIME TRANSPORT :

IMDG

UN no :1719

UN proper shipping name : CAUSTIC ALKALINE LIQUID, N.O.S. (Sodium hydroxide+Sodium hypochlorite)

Class : 8



Packing group : II

Marine pollutant : Yes (Sodium hypochlorite)

Special precautions for user : No information.

EmS number : F-A, S-B

Comply with the provisions of the IMDG on the physical separation of materials.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code :

Not concerned

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations relating to the hazards from major accidents :

Directive 96/82/EC amended by Directive SEVESO 2 (2003/15/EC)

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

Regulations relating to the classification, packing and labelling of substances and mixes :

Regulation 1272/2008/EC amended, Directive 1999/45/EC amended.

Waste regulations :

Directive 2008/98/EC of 19/11/2008 relating to waste.

Decision 2000/532/EC amended which establishes the list of hazardous waste.

Protection of workers :

Directive 98/24/EC of 07/04/1998 on the protection of the health and safety of workers from the risks related to chemical agents at work.

Regulation 850/2004/EC on persistent organic pollutants and modifying Directive 79/117/EC : Not concerned

Regulation 2037/2000/EC on substances that deplete the ozone layer : Not concerned

Regulation (EC) 648/2004 :

In conformity with the regulation in force on detergents: Regulation (EC) N° 648/2004.

Ingredient datasheet for the medical staff is available upon written request.

Contains :

5-15% Chlorine-based bleaching agents

< 5% Phosphonates, Polycarboxylates

Disinfectants

15.2. Chemical safety assessment

No

SECTION 16: Other information

The safety data sheet is additional to the technical data sheet but does not replace it. The information given here in is to the best of our knowledge correct and is given in good faith. We must also draw the user's attention on potential risks of the product is used for other purposes for which the product is known.

In no way does it exempt users from being aware of and complying with regulations applicable to their activity. It is their sole responsibility to take all necessary precautions in accordance to the usage of the product they are aware of.

Regulations are only stated in order to help users fulfill the duties involved in the use of the product.

This description should not be considered as exhaustive. It does not exempt users from ensuring if other demands need to be complied with-according to other laws than the ones hereby stated and applicable to holding and usage of the product-demands for which they will remain sole responsibility.

Section(s) modified compared with the previous version :

Revision of the safety data sheet according to 453/2010/EC Regulation.

List of R phrases referred to in sections 2 and 3 :

R31 : Contact with acids liberates toxic gas.

ALKACLEAN

Code: 6 041 3

Material Safety Data Sheet compliant with Regulation (EC) 1907/2006, Annex II, amended by Regulation (EC) 453/2010

Version 5.0.0

Revision: 31/03/15

Print Date : 31/03/15

R34 : Causes burns.

R35 : Causes severe burns.

R37 : Irritating to respiratory system.

R50 : Very toxic to aquatic life.

List of H phrases referred to in sections 2 and 3 :

H290 : May be corrosive to metals.

H314 : Causes severe skin burns and eye damage.

H335 : May cause respiratory irritation.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

Sources of key data used to compile the data sheet :

MSDS supplier

International limit values for chemical agents

Historical :

Version 5.0.0

Cancels and replaces previous version 4.1.4